

NEW

Level VI

CoC Tier 2

GaN FET Technology 200 Watt I.T.E. Series

Small Size Desktop Type

ATS200TS - □ X X X

P : C6 / C14 ← O / P Voltage
A : C8



2.5X Smaller!



Green Mode
CEC, DoE Level VI, Energy Star, ErP Stage 2, CoC Tier 2, NRCAN & GEMS Level VI
No Load Power Consumption Less Than 0.15W

- Features :**
- IEC/EN/UL 62368-1 & IEC 60950-1
 - 100-240 VAC Universal Input
 - Gallium Nitride Based Design
 - High Power Density : 12.5W / in³
250% higher than traditional adapter (5.3W / in³)
 - With 250kHz Switching Frequency
 - Efficiency up to 95%
 - Regulated Output with Low Ripple Noise
 - Modified and Custom Design Available
 - 1 Year Warranty

Model	O/P Voltage	O/P Current	Watt
ATS200TS-□120	12.0V	16.0A	192W
ATS200TS-□180	18.0V	11.1A	200W
ATS200TS-□190	19.0V	10.5A	200W
ATS200TS-□191	19.5V	10.2A	200W
ATS200TS-□200	20.0V	10.0A	200W
ATS200TS-□240	24.0V	8.3A	200W
ATS200TS-□480	48.0V	4.2A	200W
ATS200TS-□560	56.0V	3.6A	200W

Input

Voltage	100-240VAC
Line Frequency	50-60Hz
Current	2.4A Max.
Protection	Internal Primary Current Fuse
Configuration	IEC60320/C6, C8, C14

Output

Load Regulation	±5% (Typical)
Ripple & Noise	1% Vp-p Max. for Output Voltage @ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection / Over Temperature Protection
DC Cord	UL 2095 / UL 2464 / 16AWG / 18AWG
Ferrite Core	Yes

Safety Approvals
CB / UL / cUL / FCC / GS / CE / PSE / BSMI / CCC

Electrical

Topology	LLC
Dielectric Withstand	3000VAC Primary - Secondary
Leakage Current	0.25mA @ 2Pin / 3.5mA @ 3Pin
EMC Standards	EN55032
	EN61000-3-2,3
	EN55024
MTBF	300,000 Calculated Hours at 25°C , by Telcordia SR-332

Environmental

Operating Temperature	0 to + 40°C
Storage Temperature	-20 to + 80°C
Relative Humidity	Operating : 20 to 80% RH
	Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

Mechanical

Case Dimension	C6 & C14 - L 161 x W 54 x H 33 (mm)
	C8 - L 150 x W 54 x H 33 (mm)
Weight	560g (Ref.)